

03/31/00

JCS15 U.S. PTO

UTILITY  
PATENT APPLICATION  
TRANSMITTAL

Only for new nonprovisional applications under 37 CFR 1.53(b)

Attorney Docket No.

36J.P269

First Named Inventor or Application Identifier

Todd D. Newman

Express Mail Label No.

EL582469848US

JCS15 U.S. PTO  
09/540012

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

## ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 202311. ☒ Fee Transmittal Form  
(Submit an original, and a duplicate for fee processing)2. ☒ Specification Total Pages 513. ☒ Drawing(s) (35 USC 113) Total Sheets 94. ☒ Oath or Declaration Total Pages 2

- a. ☐ Newly executed (original or copy)
- b. ☒ Unexecuted for information purposes
- c. ☐ Copy from a prior application (37 CFR 1.63(d))  
(for continuation/divisional with Box 17 completed)  
[Note Box 5 below]

i. ☐ DELETION OF INVENTOR(S)  
Signed Statement attached deleting  
inventor(s) named in the prior application,  
see 37 CFR 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference (useable if Box 4c is checked)  
The entire disclosure of the prior application, from which a copy  
of the oath or declaration is supplied under Box 4c, is considered  
as being part of the disclosure of the accompanying application  
and is hereby incorporated by reference therein.

Express Mail mailing label number EL582469848US

Date of Deposit March 31, 2000

I hereby certify that this paper or fee is being deposited with  
the United States Postal Service "Express Mail Post Office to  
Addressee" service under 37 CFR 1.10 on the date indicated above  
and is addressed to the Commissioner of Patents and Trademarks,  
Washington, D. C. 20231.

Dennis A. Doherty Reg. No. 10595  
(Typed or printed name of person mailing paper or fee)

(Signature of person mailing paper or fee)

6. ☐ Microfiche Computer Program (Appendix)7. Nucleotide and/or Amino Acid Sequence Submission  
(if applicable, all necessary)

- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☐ 5 Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application  
Statement(s) Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)  
(if foreign priority is claimed)
16. ☐ Other: \_\_\_\_\_

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. \_\_\_\_/\_\_\_\_

## 18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label 05514  
(Insert Customer No. or Attach bar code label here) or ☐ Correspondence address below

NAME

Address

City

State

Zip Code

Country

Telephone

Fax



CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	240-20 =	220	X \$ 18.00 =	\$ 3,960.00
	INDEPENDENT CLAIMS (37 cfr 1.16(b))	7-3 =	4	X \$ 78.00 =	\$ 312.00
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			\$260.00 =	\$ 260.00
				BASIC FEE (37 CFR 1.16(a))	\$ 690.00
			Total of above Calculations =		\$ 5,222.00
	Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).				
	TOTAL =				\$ 5,222.00

19. Small entity status

- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.


20. ☒ A check in the amount of \$ 5,222.00 to cover the filing fee is enclosed.

21. ☐ A check in the amount of \$ \_\_\_\_\_ to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☒ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

**SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED**

NAME	Dennis A. Duchene, Reg. No. 40,595
SIGNATURE	
DATE	March 31, 2000

"Express Mail" mailing label number EL582467848US  
Date of Deposit March 31, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D. C. 20231.

Dennis A. Duchene Reg. No. 40,595  
(Typed or printed name of person mailing paper or fee)  
D. Duchene  
(Signature of person mailing paper or fee)

COLOR MANAGEMENT SYSTEM USING MEASURED DEVICE DATA

BACKGROUND OF THE INVENTION

5 Field Of The Invention

The present invention relates to a color management system for transforming color data, wherein the color management system utilizes measured colorimetric data and viewing condition data corresponding to a source device for generating appropriate color transforms for use in a color transformation sequence to transform color image data into a destination device color space. In this manner, a color transform corresponding to the source device is not generated until it is required by a color management system for transforming color image data into a destination device color space.

20 Incorporation By Reference

Commonly-owned U.S. patent application Serial No. \_\_\_\_\_, entitled "Standardized Device

0054001 033100

Characterization," by John S. Haikin, is incorporated herein by reference.

Description Of The Related Art

5           Typically, color management systems provide a means for representing a color image that was produced by a source device on a destination device. The color characteristics of the source device and the destination device for rendering colors is  
10           usually different because the devices use different colorants to render the colors, such as a printer and a monitor, or are of different manufacturers such that colors are rendered according to different techniques. To accommodate the different color  
15           characteristics of the two different devices, a color management system is typically used to modify the color image data from the source device so that it can be rendered on the destination device so as to produce a color image which appears similar in  
20           nature as the color image rendered by the source device.

          Many currently-used color management systems, such as those that support the International Color Consortium (ICC) specifications,  
25           use data files known as "device color profiles" to store information which reflects the color characteristics corresponding to a specific device. Figure 1 depicts a device color profile 1 typically used in conventional color management systems.  
30           Specifically, the color characteristic information is provided in color transform 2 which reflects the color characteristics of the source device in relation to a standard, device-independent color space. The color transform can then be used to  
35           transform color image data from the source device color space into the device-independent color space as a first step in a comprehensive transformation

00540042 099400

sequence to ultimately generate color image data in destination device color space for rendering by the destination device. Color profile 1 also includes gamut boundary descriptor 3 which describes the gamut boundary of the device.

The color transform of a color profile corresponding to a particular device is typically in the form of color transformation data which is generated by a profile-building program. It should be noted that there are several different types of profile-building programs for generating color transformation data. A profile-building program constructs the color transformation data for a particular device from corresponding sets of input color value data and output color value data in conjunction with data reflecting expected viewing conditions. The corresponding sets of input color value data and output color value data reflect the color rendering characteristics of the device in relation to a standard, device-independent color space. The many different profile-building programs currently in use often utilize different methods and techniques to generate color transformation data, some of which are proprietary. For example, a profile-building program may incorporate a technique for generating color transformation data which produces the best result for a particular device or a particular type of image as determined by the manufacturer or developer of the profile-building program.

The color transformation data built by the profile-building program is then used to transform color data values from a source device color space to a particular, device-independent color space, and visa versa. Therefore, the construction of a color transform involves the selection of a particular color space and a color appearance model.

Currently, there are several standard color spaces and color appearance models from which to select. In addition, the specifications for currently known, standard color spaces and color appearance models are in a state of rapid evolution. As a result, there currently exists a great number of profile-building programs for generating color transformation data based on different combinations of standard color spaces and color appearance models; and the number is rapidly increasing. In addition to the different choices of color spaces and color appearance models, there are many different ways to represent color transformation data in a device profile. For example, the color transformation data may be represented in a color look-up table, a polynomial function, or a sequence of single- and/or multi-variate transforms of arbitrary complexity.

To further complicate matters, many color management systems are designed to reduce processing overhead during the transformation of color image data by optimizing the color transformation data in order to increase the speed of the transformation process. The color transformation data is commonly optimized by eliminating a certain amount of unnecessary and/or less important color data as determined by the developer of the profile-building program. In addition, special proprietary functionality may be implemented into the profile-building program in order to provide more accurate color transformation from a source device color space to a destination device color space in order to achieve a preferred reproduction of the color image on the destination device. Therefore, it can be appreciated that the color transformation data contained in device color profiles corresponding to two separate devices may be quite different even

00540042 033400

though the two devices are very similar in nature,  
due to the use of two uniquely different profile-  
building programs to generate the color  
transformation data contained in each device color  
profile.

Device color profiles are typically  
structured in a standardized format in order to  
allow many different color management systems to use  
color profiles which were built by many different  
profile-building programs. The ICC has defined and  
standardized a color profile format in order to  
allow for the efficient interchange of color images  
from one device to another via color management  
systems. The ICC color profile format, however, is  
based on the assumption that the originator of the  
color image data in the source device knows what the  
best appearance of that color image data on a  
destination device should be, regardless of the  
actual destination device subsequently used to  
render the color image. This assumption is made  
because the ICC color profile format contains color  
transformation data which assumes a particular,  
standard color space and a particular appearance  
model for mapping (transforming) the color image  
data into that color appearance space.

Currently, digital color image data is  
widely used in computer and networked computing  
environments, and the use of such color image data  
is growing rapidly. Color image data corresponding  
to color images are often archived or placed into  
stock photography banks for subsequent access and  
utilization by other users. The use of such color  
image data by a subsequent user can present  
significant problems when the subsequent user  
attempts to transform the color image data into the  
color space of a destination device for rendering a  
preferred reproduction of the color image. In

5  
10  
15  
20  
25  
30  
35

In addition to the above problems, the representation of the color transformation data in the source device color profile may have been implemented in a particular manner, such as a three-dimensional color look-up table, which is not sufficiently accurate to generate an optimal color transformation sequence. Moreover, even if the source device color profile associated with the color image data and the destination device color profile are fully compatible, a subsequent user of the color image data may wish to generate a different, preferred appearance of the color image, often referred to as a preferred reproduction. Such a preferred reproduction is typically not possible, or is very difficult, when using conventional color profiles because a source device color profile corresponding to the color image data incorporates a



5  
10  
15  
20  
25  
30  
35

The present invention addresses the foregoing problems by providing a color management system for transforming source color image data, wherein the color management system directly accesses and utilizes a source device color data file containing source device color characteristic data and viewing condition data and then constructs an appropriate source color transform for use in a color transformation sequence to transform source color image data into a destination device color space.

According to one embodiment of the invention, a color management system is provided to transform source color image data from a source device into destination color image data for rendering by a destination device. A source color data file corresponding to the source device is accessed, the source color data file containing source device color characteristic data, a source color transform is constructed based on the source device color characteristic data contained in the source color data file, and the source color transform is applied to the source color image data to transform the source color image data from a source device color space into interim color image data in an interim color space.

Preferably, the source color data file is in a predetermined format having tags corresponding to the source device color characteristic data. A set of viewing condition data is preferably also included in corresponding tags of the source color data file. The source color transform is preferably either applied directly to the source color image

data or incorporated into a color transformation sequence for application to the source color image data. Preferably, the source device color characteristic data contains measured colorimetric data and corresponding device signal data. In the alternative, the source device color characteristic data represents spectral measurement data corresponding to the source device.

By virtue of this arrangement, a color management system is provided whereby raw colorimetric measurement and device signal data corresponding to a source device is stored in a standardized, formatted color data file for subsequent use by a color management system to generate a source device color transform. In this manner, the color management system is not forced to use a color transform that was originally created when the color image data was generated by the source device. A subsequent user of the color image data is therefore free to use a color management system having a preferred combination of a color space, a color appearance model and a desired set of viewing conditions in order to create a source device color transform. Accordingly, a source device color transform does not have to be created until the color image data is subsequently accessed for use by a subsequent user. In this manner, a set of color image data is associated with a corresponding source color data file that contains color characteristic data of the source device in a well recognized, robust format for use by a variety of current, and not yet known, color management systems.

According to another embodiment of the invention, a color management system is provided for managing color data to transform source color image data from a source device into destination color

004004 0340

image data for rendering by a destination device. A source color data file corresponding to the source device is accessed, the source color data file being formatted according to a standard predetermined  
5 format and having a plurality of tags containing source device color characteristic data and a set of viewing condition data corresponding to a set of viewing conditions in which the source device color characteristic data was measured. A source color  
10 transform is constructed based on the source device color characteristic data and the set of viewing condition data by utilizing an interim color space and a color appearance model, the source color transform for transforming the source color image  
15 data from a source device color space into an interim color space. The source color transform is incorporated in a color transformation sequence which is applied to the source color image data to transform the source color image data from the  
20 source device color space into a destination device color space.

Preferably, the source color data file is in a predetermined format having tags corresponding to the source device color characteristic data. A  
25 set of viewing condition data is preferably also included in corresponding tags of the source color data file. The source color transform is preferably either applied directly to the source color image data or incorporated into a color transformation  
30 sequence for application to the source color image data. Preferably, the source device color characteristic data contains measured colorimetric data and corresponding device signal data. In the alternative, the source device color characteristic  
35 data contains spectral measurement data corresponding to the source device.

00540012 033400

By virtue of this arrangement, a color management system is provided whereby raw colorimetric measurement and device signal data corresponding to a source device is stored in a standardized, formatted color data file for subsequent use by a color management system to generate a source device color transform. In this manner, the color management system is not forced to use a color transform that was originally created when the color image data was generated by the source device. A subsequent user of the color image data is therefore free to use a color management system having a preferred combination of a color space, a color appearance model and a desired set of viewing conditions in order to create a source device color transform. Accordingly, a source device color transform does not have to be created until the color image data is subsequently accessed for use by a subsequent user. In this manner, color image data is identified with a corresponding source color data file that contains color characteristic data of the source device in a well recognized, robust format for use by a variety of current, and not yet known, color management systems.

According to yet another embodiment of the invention, a memory is provided for access by a color management system, the color management system for transforming source color image data from a source device into destination color image data for rendering by a destination device. The memory includes a colorimetric data structure stored in the memory, the colorimetric data structure being formatted according to a predetermined format and containing a set of device color characteristic data elements representing a set of color characteristics of a color device and a set of viewing condition

data elements representing a set of viewing conditions of a color device.

Preferably, the colorimetric data structure is in a predetermined format having tags corresponding to the device color characteristic data elements. A set of tags corresponding to the viewing condition data elements is preferably also included. Preferably, the device color characteristic data elements are represented in CIE XYZ color space or a linear transform thereof. In the alternative, the device color characteristic data elements contain spectral measurement data elements representing spectral measurement values corresponding to a color device. The memory having the colorimetric data structure is preferably in the form of a computer-readable medium such as a hard disk, floppy disk, CD-ROM or a file in a file server which is accessible via the internet.

By virtue of this arrangement, raw colorimetric measurement data corresponding to a color device is stored in a standardized, formatted color data file for subsequent use by a color management system to generate a source device color transform. In this manner, a color management system is not forced to use a color transform that was originally created when the color image data was generated in the source device. A subsequent user of the color image data is therefore free to use a color management system having a preferred combination of a color space, a color appearance model and a set of desired viewing conditions in order to create a source device color transform. The aforementioned features provide subsequent users with the ability to control the type of source color transform used in transforming the color image data into another color space. Furthermore, a set of color image data is associated with a corresponding

color data file that contains color characteristic data of the source device in a well recognized, robust format for use by a variety of current, and not yet known, color management systems.

5           Another embodiment of the present invention provides a memory for access by a color management system, the color management system for transforming source color image data from a source device into destination color image data for rendering by a destination device. The memory includes a set of source color image data stored in the memory, and a colorimetric data structure stored in the memory, the colorimetric data structure formatted according to an extended CGATS/IT8 format including a set of tags corresponding to a set of device color characteristic data elements representing a set of measured color characteristics of the source device, and including a set of tags corresponding to a set of viewing condition data elements representing a set of viewing conditions in which the device color characteristic data elements were measured.

15           Preferably, the device color characteristic data elements are represented in CIE XYZ color space or a linear transform thereof. In the alternative, the device color characteristic data elements contain spectral measurement data elements representing spectral measurement values corresponding to the source device. The memory having the colorimetric data structure is preferably in the form of a computer-readable medium such as a hard disk, floppy disk, CD-ROM or a file in a file server which is accessible via the internet.

25           By virtue of this arrangement, raw colorimetric measurement data corresponding to a color device is stored in a standardized, formatted color data file for subsequent use by a color management system to generate a source device color

transform. In this manner, a color management system is not forced to use a color transform that was originally created when the color image data was generated in the source device. A subsequent user of the color image data is therefore free to use a color management system having a preferred combination of a color space, a color appearance model and a set of desired viewing conditions in order to create a source device color transform. The aforementioned features provide subsequent users with the ability to control the type of source color transform used in transforming the color image data into another color space. Furthermore, a set of color image data is associated with a corresponding color data file that contains color characteristic data of the source device in a well recognized, robust format for use by a variety of current, and not yet known, color management systems.

This brief summary has been provided so that the nature of the invention may be understood quickly. A more complete understanding of the invention can be obtained by reference to the following detailed description of the preferred embodiment thereof in connection with the attached drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a diagram for explaining a typical device color profile used in conventional color management systems.

Figure 2 is a representative view of a networked computer system in which the present invention may be implemented.

Figure 3 is a detailed block diagram for providing an explanation of the internal

architecture of the computer equipment shown in the computer system of Figure 1.

Figure 4 is a view for illustrating a color data file according to one embodiment of the present invention.

Figure 5 is a detailed block diagram for providing an explanation of an embedded color data file according to one embodiment of the present invention.

Figure 6 is a detailed block diagram for providing an explanation of a color management system according to one embodiment of the present invention.

Figure 7 is a flowchart for providing a detailed explanation of the color management system shown in Figure 6.

Figure 8 is a detailed block diagram for providing an explanation of a color management system according to another embodiment of the present invention.

Figure 9 is a flowchart for providing a detailed explanation of the color management system shown in Figure 8.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is generally directed to a color management system for transforming source color image data, wherein the color management system directly accesses and utilizes a source device color data file containing source device color characteristic data and viewing condition data and then constructs an appropriate source color transform for use in a color transformation sequence to transform source color image data into a destination device color space. In this manner, source color image data can be archived and an associated source color transform is not constructed



until it is subsequently needed by a color management system for transforming the source color image data into a destination device color space. A subsequent user of the archived source color image data can thereby select and/or control the type of color management system used to construct the source color transform based upon a desired combination of a color appearance space, a color appearance model and a desired set of viewing conditions. The present invention may be implemented in an output device driver, such as a printer driver contained in a computing device, or the present invention may be implemented in a color management software application module for use in a general purpose computer. It can be appreciated that the present invention is not limited to the aforementioned embodiments and that the present invention may be implemented in other forms as well.

Figure 2 is a view showing the external appearance of a representative computing system including computing equipment, peripherals and digital devices which may be used in connection with the practice of the present invention. Computing equipment 40 includes host processor 41 which comprises a personal computer (hereinafter "PC"), preferably an IBM PC-compatible computer having a windowing environment such as Microsoft Windows 2000, Windows NT, Windows 98 or Windows 95, although it may be a Macintosh or a non-windows-based computer. Provided with computing equipment 40 are color monitor 43 including display screen 42, keyboard 46 for entering text data and user commands, and pointing device 47. Pointing device 47 preferably comprises a mouse for pointing and for manipulating objects displayed on display screen 42.

Computing equipment 40 includes a computer-readable memory medium such as computer fixed disk

45 and/or floppy disk drive 44. Floppy disk drive 44 provides a means whereby computing equipment 40 can access information, such as image data, computer-executable process steps, application programs, etc. stored on removable memory media. A similar CD-ROM interface (not shown) may be provided for computing equipment 40 through which computing equipment 40 can access information stored on removable CD-ROM media.

Printer 50 is a printer, preferably a color bubble jet printer, which forms color images on a recording medium such as paper or transparencies or the like. The invention is usable with other printers, however, so long as the printer is capable of being interfaced to computing equipment 40. In addition, digital color scanner 70 is provided for scanning documents and images into computing equipment 40 and digital color camera 60 is provided for sending digital images to computing equipment 40. Of course, computing equipment 40 may acquire digital image data from other sources such as a digital video camera or from a local area network or the Internet via network interface bus 80.

Figure 3 is a detailed block diagram showing the internal architecture of host processor 41 of computing equipment 40. As shown in Figure 3, host processor 41 includes central processing unit (CPU) 113 which interfaces with computer bus 114. Also interfacing with computer bus 114 are fixed disk 45, network interface 109, random access memory (RAM) 116 for use as main memory, read only memory (ROM) 117, floppy disk interface 119, display interface 120 to monitor 43, keyboard interface 122 to keyboard 46, mouse interface 123 to pointing device 47, scanner interface 124 to scanner 70, printer interface 125 to printer 50, and digital camera interface 126 to digital camera 60.

5

10

15

20

25

30

35

for performing processing of color image data, such as one of application programs 131.

Figure 4 is a view for illustrating one embodiment of a color data file according to the present invention. In contrast to the device color profile of Figure 1, the color data file depicted in Figure 4 contains raw color characteristic data and viewing condition data corresponding to a color device. In this manner, a subsequent user of an archived color image is not forced to use a previously-generated color transform corresponding to the source device that created the archived color image. Instead, the color data file of the present invention allows a subsequent user of the archived color image to select and use a color management system having a preferred combination of a color space, a color appearance model and a set of desired viewing conditions in order to create a source device color transform for use in transforming the archived color image data into the color space of a particular destination device.

The color data file of the present invention is preferably a formatted file containing tags for the various data elements included therein, including tags for the raw color characteristic data and viewing condition data corresponding to a color device. Currently, a standardized data file format, known as CGATS/IT8, exists for storing color characteristic data corresponding to a color device. The CGATS/IT8 standard includes tags for storing measured colorimetric data corresponding to a color device. For example, the CGATS/IT8 format can be used in a colorimetric measurement scenario in which an array of color patches generated by a color device is measured and the measured colorimetric data corresponding to each color patch is stored in a color data file having the CGATS/IT8 format. In

this manner, the colorimetric data is stored in a standardized fashion for future reference and use.

None of the CGATS/IT8 standards provide tags for containing both device control signals of the color device and corresponding measured colorimetric data. For example, it is often desirable to correlate a set of printer input signals to a set of colorimetric data measured from the rendered color image that was generated in response to the printer input signals. These correlated sets of data can then be used to generate a color transform for modeling the printer's color characteristics and capabilities. In this regard, commonly-owned U.S. patent application Serial No. \_\_\_\_\_, entitled "Standardized Device Characterization," by John S. Haikin, provides an extended CGATS/IT8 format standard which includes tags for containing device control signals of a color device, in addition to the other extensions described therein. In a similar manner, the present invention utilizes extensions to the CGATS/IT8 format including tags for device control signal data as well as tags for viewing condition data. In this manner, the extended CGATS/IT8 format of the present invention contains color characteristic data and viewing condition data corresponding to a color device for use in the subsequent creation of a color transform corresponding to the color device.

Turning to Figure 4, a color data file corresponding to the present invention is depicted. It can be seen from Figure 4 that color data file 400 is organized in a formatted fashion corresponding to a predetermined format so as to include header portion 401, format portion 410 and data portion 420. Header portion 401 includes a format descriptor to describe the format of color data file 400, which in this example is a format for

5

10

35

5 Preferably, the viewing conditions represent the viewing conditions measured at the time that the device signal data elements, such as RGB data 412, and the measured colorimetric data elements, such as XYZ data 413, were recorded. In this manner, the viewing conditions in which the color device was measured can be stored in the same file with the device signal data and measured colorimetric data for future use.

WHITE\_POINT data 430 is a white point colorimetric specification corresponding to the viewing condition white point. AMBIENT data 432 is an ambient colorimetric specification corresponding to ambient viewing conditions. SURROUND data 431 corresponds to surround colorimetric specification for representing the remainder of the visual field outside the background surrounding the color sample being measured. BACKGROUND data 433 corresponds to background colorimetric specification for a background of the color sample being measured. The background commonly includes an area immediately adjacent to the point being measured out to approximately 10 degrees. LUMINANCE\_OF\_ADAPTING\_FIELD 434 represents an adapting field colorimetric specification corresponding to the state of adaption of a scene in which the sample point is being measured. Such viewing condition measurements are commonly known in the art of color management. The aforementioned array of viewing conditions enables a subsequent user of color data file to properly use the color characteristic data contained in color data file 400 for constructing a proper characterization of the color device to which color data file 400

corresponds. For example, if color data file 400 corresponds to a printer, then RGB data 412, XYZ data 413, and viewing condition data 430 to 434 can be accessed and utilized in order to create a proper color transform for transforming color image data generated by the printer into another color space, such as a profile connection space.

Data portion 420 of color data file 400 is seen to have corresponding data values for each of the aforementioned fields described in Format Portion 410. Specifically, a row of data in data portion 420 corresponds to a measured color image sample identified as A01 for SAMPLE\_ID 421. Similarly, device signal data represented by RGB data 412 is provided in RGB values 422, and measured colorimetric data represented by XYZ data 413 is provided in XYZ data 423.

In this embodiment, RGB data 412 and XYZ data 413 represent device signal data and measured colorimetric data, respectively. In the alternative, these fields can be used to contain spectral measurement values corresponding to the color device. In addition, viewing condition fields 430 to 434 can be used to represent a desired set of viewing conditions in the case that RGB data 412 and XYZ data 413 contain spectral measurement values. In this manner, color data file 400 has the flexibility to represent color characteristic data of a color device in different forms.

It can be appreciated that color data file 400 can be maintained in a memory area, such as a floppy disk, hard disk, CD-ROM, or a network server for access in a networked computing environment, including the Internet and World Wide Web. Preferably, color data file 400 is embedded in a color image file containing a set of color image data for representing a color image. In this



regard, Figure 5 depicts color image file 500 in which color data file 511 is embedded. In particular, color image file 500 includes header 510 and color image data 512 which corresponds to a color image. Header 510 includes a tag for containing color data file 511, color data file 511 corresponding to a color data file as depicted in Figure 4. In this manner, color data file 511 corresponds to the source color device, such as a digital camera or scanner, which generated color image data 512. Color image file 500 therefore provides a convenient package for combining color image data 512 with the color characteristic and viewing condition data corresponding to the source color device which generated color image data 512. It can be appreciated that color image file 500 is beneficial for storing and archiving color image data such that, regardless of the amount of time elapsed since the generation of color image data 512, a subsequent user can access color image file 500 and then access and utilize the color characteristic data and viewing condition data contained in color data file 511 to create an appropriate color transform for use in working with color image data 512. In this manner, a subsequent user of color image data 512 is not constrained to using an outdated color transform corresponding to color image data 512, or a color transform which produces sub-optical results with the subsequent user's color management system.

Figure 6 provides a detailed block diagram for illustrating the use of a color data file according to the present invention in a color management system. Turning to Figure 6, it can be seen that source color image file 62 is accessed from color image archive 61 for use by a subsequent user. For example, a graphic artist may browse

color image archive 61 and choose source color image  
file 62 corresponding to a color image that the  
graphic artist wishes to use in a composition image.  
Source color image file 62 contains color data file  
5 63 corresponding to a source device as described in  
Figure 4 and also contains color image data 64. In  
this example, source color image file 62 corresponds  
to a source device, and color image data 64 is in  
the RGB color space associated with the source  
10 device (digital camera or scanner).

Color management module 60 is then utilized  
for performing color management of color image data  
64 contained in source color image file 62.  
Specifically, as discussed above, a subsequent user  
15 of source color image file 62 can select and/or  
control a preferred color management module  
depending on the color appearance space and color  
appearance model that the subsequent user wishes to  
apply to create a source color transform from color  
20 data file 63. As represented in Figure 6, color  
data file 63 is passed to color transform generator  
65 which is a function of color management module  
60. Color transform generator 65 utilizes color  
appearance space 66 and color appearance model 67 in  
25 order to construct source color transform 68 based  
on the source device color characteristic data and  
viewing condition data contained in color data file  
63 as depicted in Figure 4.

In particular, device signal data  
30 represented by RGB data and measured colorimetric  
data represented by XYZ data are accessed from color  
data file 63 for use by color transform generator  
65. In addition, viewing condition data is accessed  
from color data file 63 for use in conjunction with  
35 the device signal data and measured colorimetric  
data in order to generate source color transform 68  
for transforming color image data 64 into color

appearance space 66. In this example, color  
appearance space 66 is a profile connection space.  
In addition, color appearance model 67 is used to  
define the source color transform 68. Source color  
transform 68 may be represented in the form of a  
look-up table, or in other forms, such as a  
polynomial function, a single-variate transform, or  
a multi-variate transform. In addition, it can be  
appreciated that color appearance space 66 can be  
any one of a number of different types of color  
appearance spaces such as a CIE Lab color space, or  
a color space composed of a lightness component, and  
two orthogonal color components for defining a  
chroma and a hue, such as Jch and Jab color spaces.  
The present invention is not limited to the use of  
the aforementioned color appearance spaces, and it  
can be appreciated that other color appearance  
spaces may be used, including other types of device-  
independent color spaces.

Color transform generator 65 of color  
management module 60 generates source color  
transform 68 in accordance with a particular color  
transform generation method and/or algorithm. It  
can be appreciated that color management module 60  
may implement any one of a different number of color  
transform generation methods and/or algorithms.  
Such color transform generation methods and/or  
algorithms may include one or more optimization  
functions for optimizing source color transform 68  
to enable source color transform 68 to process color  
image data 64 in a more efficient fashion, to  
process color image data 64 so as to achieve greater  
accuracy in the reproduction of color image data 64,  
or to process color image data 64 to achieve a  
particular preferred reproduction of color image  
data 64.

Source color transform 68 is then applied to color image data 64 in order to create interim color image data 69, which in this example is in a profile connection space, thereby allowing interim color image data 69 to be further processed by other color transforms which are also in the profile connection space. Source color transform 68 can also be stored in a memory such as a floppy, hard disk, CD-ROM or the like for subsequent access by a user in order to reduce subsequent processing of color image data 64 or of other color image data files generated from the same source device. In the example illustrated in Figure 6, interim color image data 69 is further transformed by destination color transform 71 which was accessed from a typical destination device color profile 70. It can be appreciated that destination color transform 71 may alternatively be generated by color transform generator 65 if a destination color data file similar to source color data file 63 exists for the particular destination device. In any event, whether destination color transform 71 is accessed from destination device color profile 70 or is generated from color transform generator 65, interim color image data 69 is transformed into destination color image data 72. In this example, destination device color profile 70 corresponds to an ink jet printer, and destination color transform 71 therefore transforms the color image data into a CMYK color space. Destination color image data 72 can then be rendered by the destination device, which in this case is a printer.

Figure 7 is a flowchart for explaining one implementation of the color management system and color data file of the present invention as depicted in Figure 6. In step S701, the source color data file according to the present invention is accessed,

either from a separate memory area or from within a source color image file as depicted in Figure 6. In step S702, the source device color characteristic data, such as device signal data and measured colorimetric data, is extracted along with the viewing condition data from the source color data file. As previously discussed, the measured colorimetric data is preferably in XYZ color space so as to provide compatibility with both current and future color management systems. An appropriate color management module for managing the color image data to be processed is selected in step S703. The color management module can be selected based on a preexisting embedded combination of color appearance space and color appearance model that are desired by a user, or based on the manner in which the color management module constructs a color transform.

Preferably, the color management module allows a user to select from one of many different color appearance spaces and from one of many different color appearance models to create a color transform for optimal color management results (S704). In step S705, a source color transform is constructed based on the color characteristic data and viewing condition data extracted from the source color data file, in addition to the color appearance space and color appearance model utilized by the color management module. Next, it is determined whether the user wishes to save the generated source color transform for future use (S706). If the source color transform is to be saved, it can be stored in a memory area such as a hard disk, floppy, CD-ROM or network server, as discussed above (S707), and flow then passes to step S708. If the source color transform is not to be saved, flow passes to step S708 in which it is determined whether or not to apply the source color transform to the source

00540012 033100  
00T000 21004500

color image data. If the user wishes to apply the source color transform to the source color image data, the source color transform is applied to the source color image data in step S709 in order to create interim color image data.

As discussed above, the interim color image data is preferably in a profile connection space to facilitate further color management of the interim color image data. If the source color transform is not to be applied to the source color image data, flow passes to step S713 which is the end of the process. If the interim color image data is generated in step S709, flow passes to step S710 in which it is determined whether to apply a destination color transform on the interim color image data in order to generate destination color image data for rendering by a destination device, such as a printer. If a destination color transform is not to be applied, flow passes to the end in step S713. If, however, a destination color transform is to be applied, flow passes to step S711 in which a destination color transform is applied to the interim color image data, thereby generating destination color image data. As discussed above, a destination color transform may be accessed from a conventional destination device color profile which contains a destination color transform or, in the alternative, a destination color transform may be generated in the same manner as source color transform 68 of Figure 6. In such a situation, a destination color data file similar to source color data file 63 is accessed and a destination color transform is generated in a manner similar to that described above with respect to steps S701 to S705. In either case, the destination color transform is applied in order to create destination color image data.

In step S712, the destination color image data is passed to the destination device, such as a printer, for rendering of a color image. Flow then passes to the end (step S713). In this manner, it can be appreciated that a subsequent user of an archived image file can select an appropriate color management module to construct a source color transform from the color characteristic and viewing condition data contained in the source color data file, thereby achieving preferred and/or optimal color management of the color image data.

Figure 8 provides a detailed block diagram for illustrating the use of a color data file in a color management system according to another embodiment of the present invention. In this embodiment, the color data file is used to construct a color transform which is incorporated into a comprehensive color transformation sequence for application to color image data. Turning to Figure 8, it can be seen that source color image file 82 is accessed from color image archive 81 for use by a user. For example, a graphic artist may browse color image archive 81 and choose source color image file 82 corresponding to a color image that the graphic artist wishes to use in a composition image. Source color image file 82 contains source color data file 83 as described in Figure 4 and also contains color image data 84. In this example, source color image file 82 corresponds to a scanner, and color image data 84 is in RGB color space.

Color management module 80 is then utilized for performing color management of color image data 84 contained in source color image file 82. Specifically, as discussed above, a subsequent user of source color image file 82 can select and/or control a preferred color management module depending on the color appearance space and color

appearance model that the subsequent user wishes to apply to create a source color transform from color data file 83. As represented in Figure 8, color data file 83 is passed to color transform generator 85 which is a function of color management module 80. Color data processor 85 utilizes color appearance space 86 and color appearance model 87 in order to construct source color transform 88 based on the device color characteristic data and viewing condition data contained in color data file 83 as depicted in Figure 4.

In particular, device signal data represented by RGB data and measured colorimetric data represented by XYZ data from color data file 83 is accessed for use by color data processor 85. In addition, viewing condition data is accessed from color data file 83 to be used in conjunction with the device signal data and measured colorimetric data in order to generate source color transform 88 for transforming color image data 84 into color appearance space 86. In this example, color appearance space 86 is a profile connection space. In addition, color appearance model 87 is used to define source color transform 88. Source color transform 88 may be represented by a look-up table, and it can be appreciated that source color transform may be provided in other formats, such as a polynomial function, a single-variate transform, or a multi-variate transform. In addition, it can be appreciated that color appearance space 86 can be any one of a number of different types of color appearance spaces such as a CIE Lab color space, or a color space composed of a lightness component, and two orthogonal color components for defining a chroma and a hue, such as Jch and Jab color spaces. The present invention is not limited to the use of the aforementioned color appearance spaces, and it



5

10

25

30

35

subsequent access and use. In the example illustrated in Figure 8, destination color transform 89 is accessed and utilized in conjunction with source color transform 88 to create transformation sequence 91. Destination gamut description 96 is also accessed and used in conjunction with source gamut description 95 and a gamut boundary algorithm from color management module 80 to create gamut transform step 97. Gamut transform step 97 is then incorporated into transformation sequence 91. Transformation sequence 91 is then applied to color image data 84 to generate destination color image data 92 for rendering on a destination device, such as a printer. As discussed above, destination color transform 89 and destination gamut description 96 can be accessed from a typical destination device color profile 90. It can be appreciated that destination color transform 91 and destination gamut description 96 may alternatively be generated by color data processor 85 if a destination color data file similar to source color data file 83 exists for the particular destination device. In this example, destination device color profile 90 corresponds to an ink jet printer, and destination color transform 89 is used to transform color data into a CMYK color space.

Figure 9 is a flowchart for explaining the color management system and color data file according to the embodiment of the present invention as depicted in Figure 8. In step S901, the source color data file according to the present invention is accessed, either from a separate memory area or from within a source color image file as depicted in Figure 8. In step S902, the source device color characteristic data, such as device signal data and measured colorimetric data, is extracted, in addition to the viewing condition data, from the

source color data file. As previously discussed, the measured colorimetric data is preferably in XYZ color space so as to provide compatibility with both current and future color management systems. An appropriate color management module for managing the color image data to be processed is selected in step S903. The color management module can be selected based upon a preexisting embedded combination of color appearance space and color appearance model that are desired by a user, or can be selected based on the manner in which the color management module constructs a color transform.

Preferably, as depicted in step S904, the color management module allows a user to select from one of many different color appearance spaces and from one of many different color appearance models to create a color transform for optimal color management results. In step S905, a source color transform and a source gamut boundary description are constructed based on the color characteristic data and viewing condition data extracted from the source color data file, in addition to the color appearance space and color appearance model utilized by the color management module. Next, it is determined whether the user wishes to save the generated source color transform and/or source gamut boundary description for future use (S906). If the source color transform and/or source gamut boundary description is to be saved, it is stored in a memory area such as a hard disk, floppy, CD-ROM or network server, as discussed above (S907), and flow then passes to step S908.

Next, a destination color transform and a destination device gamut boundary description are accessed in step S908. As discussed above, the destination color transform and destination gamut boundary description may be accessed from a

traditional device color profile or may be generated in the same manner as the source color transform and source gamut boundary description according to steps S901 to S905 above. The source and destination gamut boundary descriptions are then used in conjunction with a gamut mapping algorithm to create a gamut transformation step for inclusion into the transformation sequence (step S909). The source color transform, the destination color transform and the gamut transformation step are then incorporated into a transformation sequence in step S910. In this manner, a comprehensive color transformation sequence is created for efficient end-to-end processing of color image data. It is then determined in step S911 whether to save the transformation sequence for future use. If so, flow passes to step S912 in which the transformation sequence is stored in a memory, such as a floppy, hard disk, CD-ROM, network server or the like. In either case, flow passes to step S913 in which it is determined whether to apply the transformation sequence to the source color image data. If yes, the transformation sequence is applied to the source color image data to generate destination color image data in step S914. If not, flow passes to the end in step S916. If destination color image data was generated in step S914, the destination color image data is forwarded to the destination device for rendering of a color image (S915). Flow then passes to the end in step S916.

The present invention therefore provides a color data file for storing raw colorimetric measurement and device signal data corresponding to a source device in a standardized, format for subsequent use by a color management system to generate a source color transform. In this manner, a color management system is not forced to use a

color transform that was originally created when the  
color image data was generated by the source device.  
A subsequent user of the color image data can then  
use a selected color management system having a  
5 preferred combination of a color space, a color  
appearance model and a desired set of viewing  
conditions in order to create a source device color  
transform. Accordingly, a source device color  
transform does not have to be created until the  
10 color image data is subsequently accessed for use by  
a subsequent user. In this manner, color image data  
is associated with a corresponding source color data  
file that contains color characteristic data and  
viewing condition data of the source device in a  
15 well recognized, robust format for use by a variety  
of current, and not yet known, color management  
systems.

The invention has been described with  
respect to particular illustrative embodiments. It  
20 is to be understood that the invention is not  
limited to the above-described embodiments and that  
various changes and modifications may be made by  
those of ordinary skill in the art without departing  
from the spirit and scope of the invention.

25

007EE0" 27004560

WHAT IS CLAIMED IS:

1. A method for managing color data to transform source color image data from a source device into destination color image data for rendering by a destination device, said method comprising the steps of:

accessing a source color data file  
corresponding to the source device, the source color  
data file containing source device color  
characteristic data;

constructing a source color transform based on the source device color characteristic data contained in the source color data file; and

applying the source color transform to the source color image data to transform the source color image data from a source device color space into interim color image data in an interim color space.

2. A method for managing color data according to Claim 1, wherein the source device color characteristic data contains measured colorimetric data and corresponding device signal data.

3. A method for managing color data according to Claim 1, wherein the color data file further contains viewing condition data corresponding to a set of viewing conditions in which the source device color characteristic data was measured.

4. A method for managing color data according to Claim 3, wherein the viewing condition data includes ambient colorimetric specification data.



12. A method for managing color data according to Claim 2, wherein the source device is a printer, wherein the device signal data represents a set of input command signal values for the printer, and wherein the measured colorimetric data represents a set of measured color values corresponding to a color image rendered by the printer.

13. A method for managing color data according to Claim 2, wherein the source device is a scanner, wherein the measured colorimetric data represents a set of measured color values corresponding to a rendered color image, and wherein the device signal data represents a set of output signal values from the scanner.

14. A method for managing color data according to Claim 1, further comprising the step of transforming the interim color image data into destination color image data in a destination device color space.

15. A method for managing color data according to Claim 1, further comprising the step of incorporating the source color transform in a color transformation sequence.

16. A method for managing color data according to Claim 15, further comprising the step of applying the color transformation sequence to the source color image data to generate destination color image data in a destination device color space.

17. A method for managing color data according to Claim 14, wherein the step of

00540042 033400





23. A method for managing color data according to Claim 1, wherein the source device color characteristic data represents spectral measurement values corresponding to the source device.

25. A method for managing color data according to Claim 24, wherein the construction of the source color transform is also based on the viewing condition data.

27. A method for managing color data according to Claim 1, wherein the construction of the source color transform utilizes a color appearance model.

29. A method for managing color data according to Claim 27, wherein the source color transform is a polynomial function.

31. A method for managing color data according to Claim 27, wherein the source color transform is a multi-variate transform.

33. A method for managing color data according to Claim 1, wherein the construction of the source color transform is optimized to increase accuracy of a transformation of the source color image data.

35. A method for managing color data according to Claim 1, wherein the source color data file is formatted according to a predetermined standardized format.

36. A method for managing color data according to Claim 35, wherein the source color data file includes a set of tags for the source device color characteristic data.

37. A method for managing color data according to Claim 35, wherein the source color data file includes a set of tags for a set of viewing condition data corresponding to a set of viewing conditions in which the source device color characteristic data was measured.

38. A method for managing color data according to Claim 35, wherein the predetermined standardized format is an extended CGATS/IT8 format.

39. A method for managing color data according to Claim 38, wherein the extended CGATS/IT8 format includes a set of tags for the source device color characteristic data.

40. A method for managing color data according to Claim 38, wherein the extended CGATS/IT8 format includes a set of tags for a set of viewing condition data corresponding to a set of viewing conditions in which the source device color characteristic data was measured.

41. A method for managing color data according to Claim 9, wherein the measured colorimetric data is in a standard color space.

42. A method for managing color data according to Claim 41, wherein the standard color space is an XYZ color space.

43. A method for managing color data according to Claim 11, wherein the measured colorimetric data is in a standard color space.

45. A method for managing color data according to Claim 1, wherein the construction of the source color transform is based on a type of the interim color space and a color appearance model.

47. A method for managing color data according to Claim 1, wherein the source color transform is stored in a memory.

49. A method for managing color data according to Claim 1, wherein a source gamut boundary description is generated from the source color data file.

50. A method for managing color data according to Claim 49, wherein the source gamut boundary description is used in conjunction with a destination gamut boundary description and a gamut mapping algorithm to create a gamut transformation.

51. A method for managing color data to transform source color image data from a source device into destination color image data for

accessing a source color data file corresponding to the source device, the source color data file being formatted according to a standard predetermined format and having a plurality of tags containing source device color characteristic data and a set of viewing condition data corresponding to a set of viewing conditions in which the source device color characteristic data was measured;

incorporating the source color transform in a color transformation sequence; and

52. A memory for access by a color management system, the color management system for transforming source color image data from a source device into destination color image data for rendering by a destination device, said memory comprising:

a colorimetric data structure stored in the memory, the colorimetric data structure being formatted according to a predetermined format and containing a set of device color characteristic data elements representing a set of color characteristics of a color device and a set of viewing condition

data elements representing a set of viewing conditions of a color device.

53. A memory according to Claim 52, wherein the set of device color characteristic data elements includes measured colorimetric data elements and corresponding device signal data elements.

54. A memory according to Claim 52, wherein the viewing condition data elements represent a set of viewing conditions in which the device color characteristic data elements were measured.

55. A memory according to Claim 54, wherein the viewing condition data elements include an ambient colorimetric specification data element.

56. A memory according to Claim 54, wherein the viewing condition data elements include a surround colorimetric specification data element.

57. A memory according to Claim 54, wherein the viewing condition data elements include a background colorimetric specification data element.

58. A memory according to Claim 54, wherein the viewing condition data elements include an adapting field colorimetric specification data element.

59. A memory according to Claim 53, wherein the device signal data elements represent a set of input command signal values for the source device.

00700"2T004550

61. A memory according to Claim 53,  
wherein the device signal data elements represent a  
set of output command signal values from the source  
device.

63. A memory according to Claim 53, wherein the source device is a printer, wherein the device signal data elements represent a set of input command signal values for the printer, and wherein the measured colorimetric data elements represent a set of measured color values corresponding to a color image rendered by the printer.

64. A memory according to Claim 53, wherein the source device is a scanner, wherein the measured colorimetric data elements represent a set of measured color values corresponding to a rendered color image, and wherein the device signal data elements represent a set of output signal values from the scanner.

65. A memory according to Claim 52, wherein the device color characteristic data elements contains spectral measurement data elements which represent spectral measurement values corresponding to the source device.



67. A memory according to Claim 52,  
wherein the colorimetric data structure is formatted  
according to a predetermined standardized format.

69. A memory according to Claim 67, wherein the colorimetric data structure includes a set of tags for a set of viewing condition data elements corresponding to a set of viewing conditions in which the device color characteristic data elements were measured.

71. A memory according to Claim 70,  
wherein the extended CGATS/IT8 format includes a set  
of tags for the device color characteristic data  
elements.

72. A memory according to Claim 70,  
wherein the extended CGATS/IT8 format includes a set  
of tags for a set of viewing condition data elements  
corresponding to a set of viewing conditions in  
which the device color characteristic data elements  
were measured.

74. A memory according to Claim 73,  
wherein the standard color space is an XYZ color  
space.

76. A memory according to Claim 75,  
wherein the standard color space is an XYZ color  
space.

78. A memory according to Claim 77,  
wherein the computer-readable medium is a floppy  
disk.

80. A memory according to Claim 77,  
wherein the computer-readable medium is a CD-ROM.

82. A memory according to Claim 81,  
wherein the networked computing environment is a  
global networked computing environment.

84. A memory according to Claim 82,  
wherein the global networked computing environment  
is the world wide web.

86. A memory according to Claim 85,  
wherein the second memory further contains a header  
having a tag corresponding to the colorimetric data  
structure.

a set of source color image data stored in the memory; and

a colorimetric data structure stored in the memory, the colorimetric data structure formatted according to an extended CGATS/IT8 format, the colorimetric data structure including a set of tags corresponding to a set of device color characteristic data elements representing a set of measured color characteristics of the source device, and including a set of tags corresponding to a set of viewing condition data elements representing a set of viewing conditions in which the device color characteristic data elements were measured.

88. An apparatus for managing color data to transform source color image data from a source device into destination color image data for rendering by a destination device, comprising:

a program memory for storing process steps executable to perform a method according to any of Claims 1 to 51; and

a processor for executing the process steps stored in said program memory.

89. Computer-executable process steps stored on a computer readable medium, said computer-executable process steps for managing color data to transform source color image data from a source device into destination color image data for rendering by a destination device, said computer-executable process steps comprising process steps executable to perform a method according to any of Claims 1 to 51.

90. A computer-readable medium which stores computer-executable process steps, the computer-executable process steps to transform source color image data from a source device into destination color image data for rendering by a destination device, said computer-executable process steps comprising process steps executable to perform a method according to any of Claims 1 to 51.

00750" 2F004550








FIG. 2




FIG. 3



HEADER PORTION 401	CAMERA MEASUREMENT		
	ORIGINATOR	"Company X"	
	DESCRIPTOR	"MyShot Camera"	
	CREATED	"03/31/00"	
FORMAT PORTION 410	NUMBER OF FIELDS	7	430
	NUMBER OF SETS	27	431
	WHITE_POINT_X	95.197, WHITE_POINT_Y 100.158, WHITE_POINT_Z 95.197,	432
	SURROUND_AVERAGE,	AMBIENT_X 95.197, AMBIENT_Y 100.158, AMBIENT_Z 109.051,	433
DATA PORTION 420	BACKGROUND_X	19.039, BACKGROUND_Y 20.032, BACKGROUND_Z 19.039	434
	LUMINANCE_OF_ADAPTING_FIELD	18.000	435
	BEGIN_DATA_FORMAT		436
	SAMPLE_ID,	RGB_R RGB_G RGB_B, XYZ_X XYZ_Y XYZ_Z,	437
	END_DATA_FORMAT		438
	BEGIN_DATA		439
	A01	127 255 127 24.213 35.692 22.919	440
	END_DATA		441

FIG. 4

COLOR IMAGE FILE 500




FIG. 5





FIG. 6








FIG. 9

**COMBINED DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION**  
(Page 1)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled \_\_\_\_\_

COLOR MANAGEMENT SYSTEM USING MEASURED DEVICE DATA

the specification of which ☒ is attached hereto ☐ was filed on \_\_\_\_\_ as  
United States Application No. or PCT International Application No. \_\_\_\_\_  
and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

<u>Country</u>	<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>(Yes/No) Priority Claimed</u>
----------------	------------------------	----------------------------	--------------------------------------

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below:

<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>
------------------------	----------------------------

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>Status (Patented, Pending, Abandoned)</u>
------------------------	----------------------------	--------------------------------------------------

**COMBINED DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION**  
(Page 2)

I hereby appoint the practitioners associated with the firm and Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

**FITZPATRICK, CELLA, HARPER & SCINTO**  
**Customer Number: 05514**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor Todd D. Newman

Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_ Citizen/Subject of United States

Residence 751 Marion Avenue, Palo Alto, CA 94303

Post Office Address c/o Canon Information Systems, Inc.

110 Innovation Drive, Irvine, CA 92612

Full Name of Second Joint Inventor, if any John S. Haikin

Second Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_ Citizen/Subject of United States

Residence 804 Bedford Street, Fremont, CA 94539

Post Office Address c/o Canon Information Systems, Inc.

110 Innovation Drive, Irvine, CA 92612

Full Name of Third Joint Inventor, if any \_\_\_\_\_

Third Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_ Citizen/Subject of \_\_\_\_\_

Residence \_\_\_\_\_

Post Office Address \_\_\_\_\_

Full Name of Fourth Joint Inventor, if any \_\_\_\_\_

Fourth Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_ Citizen/Subject of \_\_\_\_\_

Residence \_\_\_\_\_

Post Office Address \_\_\_\_\_